

B.M. - RR spike in Power Pole 26' Lt. of Station 15+80 Assumed Elev. 200.00

TOTAL SHEETS SECTION TR 95 94-01166-00-BR PULASKI 13 PROJECT NO. BROS-153(30) CONTRACT NO. 99327



Existing Structure - Timber deck with steel stringers on concrete abutments. 16.2' W x 36.0' L

* Normal to Channel ELEVATION



Skew Angle "D" = 20" Left Forward

PILE DATA (2-ABUTS.)

Type & Size: Metal Shell 12" Ø x 0.25" Walls
Nominal Required Bearing: 279 kips
Allowable Resistance Available: 93 kips
Estimated Length: 65 Feet Bent #1, 71 Feet Bent #2
Number Required: 8 (Includes 1 Test Pile
located in Bent #1)

PULASKI SLOUGH SEC. 94-01166-00-BR BUILT 20_ COUNTY UNIT ROAD DISTRICT PULASKI COUNTY LOADING HS20 STR. NO. 077-3126

LETTERING FOR NAME PLATE

Locate Name Plate at southwest Corner of Bridge (See Std. CN)

LOCATION SKETCH

WATERWAY INFORMATION

Drainage /	area =	13.636 50	7. MI. LO	w Grade	Liev. =	201.26	At	Sta. 17	+/2
Flood	Freq.	Q	Opening Sq. Ft.		Natural	Head-Ft.		Headwater El.	
	Yr.	C.F.S.	Exist.	Prop!*	H.W.E.	Exist.	Prop.	Exist.	Prop.
Design	15	2,050	111.5*	347.6	200.77	0.06	0.50	200.83	201.27
Base	100	2,990	111.5*	400.5*	201.77	0.02	0.54	201.79	202.31
Overtopping	<2	403	82.8		197.86	0.76		198.62	
Max. Calc.	500								

*Over Road Flow (Sq Ft): Exist. 614.3 1,153.6 Prop. 168.5 **Note: Flow area of proposed structure augmented with a 36" CMP. Overtopping of proposed road occurs at ±Q(15).

GENERAL NOTES

- Metal Shell piles shall meet ASTM A 252 Grade 3 specifications.
- Test Piles shall be driven to 110% of the Nominal Required Bearing indicated in the pile data.
- The Contractor shall drive one test pile, as specified, in a permanent location as directed by the Engineer before ordering the remaining piles.
- See special provisions for boring logs.
 A Corrosion inhibitor, as covered in the Standard
 Specifications, shall be used in the precast prestressed concrete deck beams.
- The Bituminous Concrete Surface Course and the Waterproofing Membrane System shown on the plans shall not be provided.

TOTAL BILL OF MATERIAL

11-11	Super	Sub.		Tota/	
Unit	Super	Piers	Abuts.	rotar	
Each					
Cu. Yds.			19.4	19.4	
Sq. Ft.	1440			1440	
Foot	120			120	
Pound			2440	2440	
Foot			479	479	
Foot			479	479	
Each			1	1	
Cu. Yds.			2.1	2.1	
Each			1	1	
Cu. Yds.			11	11	
Cu. Yds.			360	360	
Tons			189	189	
	Cu. Yds. Sq. Ft. Foot Pound Foot Foot Each Cu. Yds. Each Cu. Yds. Cu. Yds.	Each Cu. Yds. Sq. Ft. 1440 Foot 120 Pound Foot Each Cu. Yds. Each Cu. Yds. Cu. Yds.	Unit Super Piers Each Cu. Yds. Sq. Ft. 1440 Foot 120 Pound Foot Foot Each Cu. Yds. Each Cu. Yds. Cu. Yds. Cu. Yds.	Unit Super Piers Abuts. Each 19.4 Sq. Ft. 1440 19.4 Foot 120 2440 Found 2440 Foot 479 479 Each 1 1 Cu. Yds. 2.1 Each 1 1 Cu. Yds. 360	

"I certify that to the best of my knowledge, information and belief, this bridge design is structurally adequate for the design loading shown on the plans. The design is an economical one for the style of structure and complies with the requirements of the current AASHTO Standard Specifications for Highway Bridges. The capacity of the pile foundation, hydraulics and quantities were determined by Others and are not covered by this certification. As directed by the Local Agency, liquefaction potential of the sub-grade has not been considered in the structural

11-6-08 TATE OF ILLIA OF 081-005468 STRUCTURAL

Exp. 11.30.2010

the Illinois Department of Transportation. Edward W. Miller

accordance with the policies and proceedures of

PROFESSIONAL ENGINEER #062-025277

EXPIRES NOV. 30, 2009

"I certify that to the best of my knowledge, information and belief, the capacity of the pile foundation, the hydraulics calculations for the waterway opening and

the estimated quantities for this structure have been designed useing standard engineering methods in

10-1-08

ENGINEER OF (LLINOIS PITTINO13

W. MIL

25277

REGISTERED **PROFESSIONAL** LOADING HS20-44

SEISMIC DATA

DESIGN SPECIFICATIONS

2002 AASHTO Standard Specifications - 17 th ed.

Allow 25#/sq. ft. for future wearing surface

Seismic Performance Category (SPC) = B Bedrock Acceleration Coefficient (A) = 18.0% Site Coefficient (S) = 1.5

GENERAL PLAN & ELEVATION TOWNSHIP ROUTE 95 PULASKI SLOUGH SECTION 94-01166-00-BR PULASKI COUNTY STATION 15+00